



### **Description**

Extra heavy duty machine loaded with features to enhance a long working life and also capable of producing a cut above the rest.

### **Standard Features**

Heavy duty construction.

Very low profile.

Low HP usage, easy to drive due to low profile.

5ml double plating in cutting area.

Very large heavy duty hammers.

Sliding 3PL pickup point with rear mulcher support.

Rear roller with heavy duty easy change bearings.

Heavy duty bearing setup of main rotor with a unique cutter for stray wire or poly pickup.

Extra large gearbox.

Easy accessible grease points.

Large 4 drive belt setup.

### **Options**

Front level rollers with extra plating for long life.

Hydraulic side shift with hoses with Hydraulic remote plugs.

Rear rake tynes.

### **Contact**

A&A Holding








Mobile : 0418920760

Office : 08 9293 5400

Fax : 08 9293 5410



**Technical specifications:**

Cod.	Mod.						kW-HP		
OSM.001250	SM 1250 *	1250 mm	1400 mm	400 (600) mm	9	60	22 : 30	480 mm - 1250 mm -780 mm	440 kg
OSM.001350	SM 1350 *	1350 mm	1500 mm	400 (600) mm	9	60	29 : 40	480 mm - 1250 mm -780 mm	460 kg
OSM.001500	SM 1500 *	1500 mm	1650 mm	400 (600) mm	9	72	37 : 50	480 mm - 1250 mm -780 mm	480 kg
OSM.001750	SM 1750	1750 mm	1900 mm	400 (600) mm	12	84	44 : 60	480 mm - 1250 mm -780 mm	530 kg
OSM.002000	SM 2000	2000 mm	2150 mm	400 (600) mm	15	96	51 : 70	480 mm - 1250 mm -780 mm	570 kg
OSM.002250	SM 2250	2250 mm	2400 mm	400 (600) mm	15	108	59 : 80	480 mm - 1250 mm -780 mm	620 kg
OSM.002500	SM 2500	2500 mm	2650 mm	400 (600) mm	15	120	66 : 90	480 mm - 1250 mm -780 mm	660 kg